

Double braid made of soft-spun high-strength polyester, 16 x 5- to 16-mm Ø strands, 24 x 18- to 24-mm Ø strands.

ALTA TENACITÀ / HIGH-STRENGTH

For mooring and sheets. Sold in reels.

Colour.		Colour			Ø mm	m
White	Breaking load kg	Blue	Black	Breaking load kg		
06.467.05	350	06.468.05	06.469.05	350	5	200
06.467.06	500	06.468.06	06.469.06	500	6	200
06.467.08	800	06.468.08	06.469.08	720	8	200
06.467.10	1440	06.468.10	06.469.10	1200	10	200
06.467.12	2040	06.468.12	06.469.12	1800	12	200
06.467.14	2300	06.468.14	06.469.14	2000	14	100
06.467.16	2840	06.468.16	06.469.16	2500	16	100
06.467.18	4460	06.468.18	06.469.18	4000	18	100
06.467.20	5250	06.468.20	06.469.20	4500	20	100
06.467.24	7950	06.468.24	06.469.24	6800	24	100



Square Line braid made of high-strength 8-strand polyester

Ideal for mooring lines. Very easy to splice, sturdy and handy. Sold in reels.


White	Blue	Black	Ø mm	Breaking load kg	m
06.448.12	06.458.12	06.478.12	12	2000	200
06.448.14	06.458.14	06.478.14	14	2500	200
06.448.16	06.458.16	06.478.16	16	3000	100
06.448.18	06.458.18	06.478.18	18	3900	100
06.448.20	06.458.20	06.478.20	20	4600	100
06.448.22	06.458.22	-	22	5500	100
06.448.24	06.458.24	06.478.24	24	6600	80



High-strength spliced mooring line

Made of 3-strand high-strength polyester, fitted with stainless steel thimbles. Spliced by hand. Sold in reels.

Colour.		Colour			Ø mm	Length m
White	Breaking load kg	Blue	Black	Breaking load kg		
06.443.10	1300	-	-	-	10	6
06.443.11	2000	06.443.31	06.443.01	1600	12	6
06.443.12	2000	06.443.32	06.443.02	1600	12	9
06.443.13	2700	06.443.33	06.443.03	2150	14	8
06.443.14	2700	06.443.34	06.443.04	2150	14	12
06.443.15	3600	06.443.35	06.443.05	3000	16	8
06.443.16	3600	06.443.36	06.443.06	3000	16	12
06.443.19	5200	06.443.39	06.443.07	4200	20	8
06.443.20	5200	06.443.40	06.443.08	4200	20	12
06.443.24	6750	06.443.44	06.443.09	5500	24	15
06.443.28	8700	06.443.48	06.443.58	7000	28	15



OSCULATI



High-strength spliced mooring line, double braid

Made of high-strength polyester double braid fitted with stainless steel thimble. Spliced by hand.

Colour.		Colour			Ø mm	Length m
White	Breaking load kg	Blue	Black	Breaking load kg		
06.443.70	1440	06.443.80	06.443.90	1200	10	6
06.443.71	2040	06.443.81	06.443.91	1800	12	7
06.443.72	2300	06.443.82	06.443.92	2000	14	9
06.443.73	2840	06.443.83	06.443.93	2500	16	11
06.443.74	5250	06.443.84	06.443.94	4500	20	12
06.443.75	7950	06.443.85	06.443.95	6800	24	15

